


K-NEBELOELER METALLBEHAE S T VARIOB

Oil-mist lubricators with metal bowl, incl. sight glass and metal sight dome

HANSA FLEX

Omadused

| | |
|------------------------------------|--|
| Sisendrõhk | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| Aine temperatuur | max. 50 °C |
| Keskonnatemperatuur | Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl) |
| Tihendusmaterjal | NBR |
| Korpus | Die-cast zinc |
| Tilgapüüdur | PA |
| Õlisort | CL 32 acc. to DIN 51517 - ISO VG 32 |
| Läbivoolu väärtuse mõõtmine | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Tellimisinfo

Oil-mist lubricators are also available with bowl guard or metal bowl.

Artikkel

| Märgistus | Keere | Läbivool (L/min) | A (mm) | B | C (mm) |
|----------------|-------|---------------------|-----------|----------|-----------|
| K- 07 25 09 14 | G 1/4 | 3400 | 48,0 | 180,0 mm | 60,0 |
| K- 07 25 09 16 | G 3/8 | 4400 | 48,0 | 180,0 mm | 60,0 |
| K- 07 25 09 18 | G 1/2 | 4600 | 70,0 | 224,0 mm | 65,0 |
| K- 07 25 09 20 | G 3/4 | 7500 | 70,0 | 224,0 mm | 65,0 |
| K- 07 25 09 22 | G 1 | 7500 | 124,0 | 224,0 mm | 65,0 |

Varuosad

| | |
|---|-------------------------|
| K-ERSATZBEHAELTER VARIOBLOC POLY | Spare tank Polycarbonat |
| K-TROPFAUFSATZ VARIOBLOC | Drip attachment |
| K-TROPFAUFSATZ METALL | Drip attachment metal |