

K-DRV SCHNVERSCHR V RAENDEL

Unidirectional flow control valves, incoming air restriction (»V«), quick-lock screw fitting

HANSA FLEX

Omadused

| | |
|--|------------------------------------|
| Töörõhk | max 10 baari |
| Temperatuuri ulatus | 0 °C to +70 °C |
| Õõneskrui, Illgendvare, reguleerimiskrui | Nickel-plated brass |
| Sisedetail | Brass with a bare metal surface |
| O-rõngas huultihend | NBR |
| Tihendid (kadumatu) | Polyamide (glass fibre-reinforced) |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Artikkel

| Märgistus | C (mm) | Vooliku jaoks | Keere | SW | B (mm) |
|----------------|-----------|---------------|-------|-------|-----------|
| K- 07 15 05 10 | 18,0 | 4 mm / 2,5 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 05 11 | 19,0 | 5 mm / 3 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 05 12 | 19,0 | 6 mm / 4 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 05 18 | 23,0 | 5 mm / 3 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 05 19 | 25,0 | 6 mm / 4 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 05 20 | 25,0 | 8 mm / 6 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 05 15 | 26,5 | 6 mm / 4 mm | G 1/4 | 17 mm | 51,4 |
| K- 07 15 05 16 | 27,5 | 8 mm / 6 mm | G 1/4 | 17 mm | 51,4 |
| K- 07 15 05 14 | 28,5 | 10 mm / 8 mm | G 1/4 | 17 mm | 51,4 |