

K-DRV STECK V SCHLITZ

Unidirectional flow control valves, incoming air restriction (»V«), plug-in connector

HANSA FLEX

Omadused

| | |
|---|------------------------------------|
| Töörõhk | max 10 baari |
| Temperatuuri ulatus | 0 °C to +70 °C |
| Õõneskrüvi, Illigendvare, reguleerimisvõlli | Nickel-plated brass |
| Sisedetail | Brass with a bare metal surface |
| O-rõngas huultihend | NBR |
| Tihendid (kadumatu) | Polyamide (glass fibre-reinforced) |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Artikkel

| Märgistus | C (mm) | Vooliku jaoks | Keere | SW | B (mm) |
|----------------|-----------|---------------|-------|-------|-----------|
| K- 07 15 05 28 | 18,6 | 4 mm | M 5 | 8 mm | 24,5 |
| K- 07 15 05 29 | 21,7 | 6 mm | M 5 | 8 mm | 24,5 |
| K- 07 15 05 33 | 20,6 | 4 mm | G 1/8 | 14 mm | 32,0 |
| K- 07 15 05 34 | 22,7 | 6 mm | G 1/8 | 14 mm | 32,0 |
| K- 07 15 05 35 | 23,7 | 8 mm | G 1/8 | 14 mm | 32,0 |
| K- 07 15 05 31 | 24,2 | 6 mm | G 1/4 | 17 mm | 40,0 |
| K- 07 15 05 32 | 24,7 | 8 mm | G 1/4 | 17 mm | 40,0 |
| K- 07 15 05 30 | 26,8 | 10 mm | G 1/4 | 17 mm | 40,0 |
| K- 07 15 05 36 | 28,3 | 10 mm | G 3/8 | 20 mm | 50,0 |