

K-PNEU LOGIKELEMENTE

Pneumatic logic elements

HANSA FLEX

Omadused

Töörõhk	OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
Temperatuuri ulatus	-10 °C to +60 °C
Ühendus	Push-in fitting for 4 mm pipe
Läbivoolukogus	100 l/min (at 6 bar and $\Delta p = 1$ bar)
Nimi-\emptyset	2,7 mm
Lähtestamine	OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
Materjal	Technopolymer
Siiber	Aluminium
Tihendusmaterjal	NBR



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the Ω -rail (DIN EN 50022) integral with the body.

Artikkel

Märgistus	Funktsioon	Kõrgus (mm)	Pikkus (mm)
K- 07 15 13 77	OR	40	38,5
K- 07 15 13 78	AND	40	38,5
K- 07 15 13 79	NOT	40	55,2
K- 07 15 13 80	YES	40	55,2
K- 07 15 13 81	MEMORY	41	89,5