

# K-PNEU LOGIKELEMENTE

Pneumatic logic elements

**HANSA FLEX**

## Omadused

|                                    |  |
|------------------------------------|--|
| <b>Töörõhk</b>                     | OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar) |
| <b>Temperatuuri ulatus</b>         | -10 °C to +60 °C   |
| <b>Ühendus</b>                     | Push-in fitting for 4 mm pipe  |
| <b>Läbivoolukogus</b>              | 100 l/min (at 6 bar and $\Delta p = 1$ bar)  |
| <b>Nimi-<math>\emptyset</math></b> | 2,7 mm   |
| <b>Lähtestamine</b>                | OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring               |
| <b>Materjal</b>                    | Technopolymer  |
| <b>Siiber</b>                      | Aluminium  |
| <b>Tihendusmaterjal</b>            | NBR  |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the  $\Omega$ -rail (DIN EN 50022) integral with the body.

## Artikkel

| Märgistus      | Funktsioon | Kõrgus (mm) | Pikkus (mm) |
|----------------|------------|-------------|-------------|
| K- 07 15 13 77 | OR         | 40          | 38,5        |
| K- 07 15 13 78 | AND        | 40          | 38,5        |
| K- 07 15 13 79 | NOT        | 40          | 55,2        |
| K- 07 15 13 80 | YES        | 40          | 55,2        |
| K- 07 15 13 81 | MEMORY     | 41          | 89,5        |