


K-KURZH ZYL EINFACHW

Short-stroke cylinders, single-acting (magnetic)

HANSA FLEX

Omadused

Vahendid	Filtered compressed air, lubricated (ensure continuity) or unlubricated
Töörõhk	max 10 baari
Rõhk	0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)
Temperatuuri ulatus	-10 °C to +80 °C
Kolvivarras	C45 steel, hard chrome-plated
Toru	Aluminium alloy, anodised
Pea läbimõõt	Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium
Kolb	Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE
Kolvivarda tihend	NBR (additional charge for PU and FKM)
Kolvitihend	NBR (additional charge for PU and FKM)



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Suitable for installation in limited spaces, with magnet.

Lisateave

Important: The scope of supply does not include a connector. Please order separately.

Other types, e.g. increased thermal stability, non-standard strokes, through rod, non-rotating version, etc., available on request.

Artikkel

Märgistus	Kolbide Ø	Keskpunkt (mm)	Ühendus	Kolvivarda sisekeere
K- 07 15 11 87	12 mm	10	M 5	M 3
K- 07 15 11 88	12 mm	25	M 5	M 3
K- 07 15 11 89	16 mm	10	M 5	M 5
K- 07 15 11 90	16 mm	25	M 5	M 5
K- 07 15 11 91	20 mm	10	M 5	M 5
K- 07 15 11 92	20 mm	25	M 5	M 5
K- 07 15 11 93	25 mm	10	G 1/8	M 5
K- 07 15 11 94	25 mm	25	G 1/8	M 5
K- 07 15 11 95	32 mm	10	G 1/8	M 6
K- 07 15 11 96	32 mm	25	G 1/8	M 6
K- 07 15 11 97	40 mm	10	G 1/8	M 6
K- 07 15 11 98	40 mm	25	G 1/8	M 6
K- 07 15 11 99	50 mm	25	G 1/8	M 8
K- 07 15 12 00	63 mm	25	G 1/8	M 8

Lisatarvikud

K-MAGNETSENSOREN-REED Reed magnetic sensor (incl. 2.5 m cable)