

# K-SCHNELLENTLUEFTUNG V

Quick-exhaust valves

**HANSA FLEX**

## Omadused

|                 |                                |
|-----------------|--------------------------------|
| min töö rõhk    | 0,5 bar                        |
| Töö rõhk        | maks 12 baari                  |
| Töö temperatuur | Max. 80 °C                     |
| Keeme kirjeldus | G thread acc. DIN EN ISO 228-1 |
| Korpus          | Nickel-plated brass            |
| Membran         | Polyurethane                   |



## Vihje

Lisaandmed saate soovi korral.

## Artikkel

| Märgistus      | Keere | A<br>(mm) | B<br>(mm) | SW1<br>(mm) | SW2<br>(mm) | SW3<br>(mm) |
|----------------|-------|-----------|-----------|-------------|-------------|-------------|
| K- 07 30 25 18 | G 1/8 | 28,0      | 42,0      | 14          | 14          | 14          |
| K- 07 30 25 17 | G 1/4 | 33,0      | 53,0      | 19          | 19          | 19          |
| K- 07 30 25 16 | G 1/2 | 43,0      | 71,0      | 26          | 26          | 26          |

## Varuosad

|                |                             |
|----------------|-----------------------------|
| K-ERSATZ DICHT | Replacement diaphragm, seal |
|----------------|-----------------------------|