
K-STOPPVENTILE STECK

Stop valves, ports 2 and 3 with plug connection



Omadused					
Töörõhk	Max. 10 bar				
Juhtimisrõhk	1 - 5 bar, depending on operating pressure				
Aine temperatuur	max. 70 °C				
Paigaldusasend	Any. Ring pieces can still be rotated 360° after the valve has been tightened				
Tihendusmaterjal	Perbunan				





Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Artikkel						
Märgistus	Port 1	Port 2	Ühendus 3	Materjal	B (mm)	C (mm)
K- 07 15 20 50	G 1/8	6 mm	4 mm	Nickel-plated brass	52,0	25,0
K- 07 15 20 49	G 1/4	6 mm	4 mm	Nickel-plated brass	58,0	28,0
K- 07 15 20 51	G 3/8	8 mm	4 mm	Nickel-plated brass	63,0	32,0
K- 07 15 20 48	G 1/2	12 mm	4 mm	Nickel-plated brass	72,0	41,0

14.12.2025 HANSA-FLEX AG www.hansa-flex.com