

# K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC

**HANSA FLEX**

## Omadused

<b>Töörõhk</b>	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
<b>Temperatuuri ulatus</b>	-10 °C to +60 °C
<b>Läbivool 6 bar ja 10 bar</b>	550 NI/min
<b>Läbivool 6 bar ja 5 bar</b>	400 NI/min
<b>Ventiilikorpus</b>	Alumiinium
<b>Vedru</b>	Special steel
<b>Kolb</b>	Aluminium
<b>Tihendusmaterjal</b>	NBR



## Vihje

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Lisaandmed saate soovi korral.

## Lisateave

Important: The scope of supply does not include a connector. Please order separately.

## Artikkel

Märgistus	Ühendus	Sümbol	Rakendus	Lülitusasendid
K- 07 15 00 78	G 1/8	5	monostable	2
K- 07 15 00 79	G 1/8	6	bistabiilne	2
K- 07 15 00 80	G 1/8	7	monostable	3*
K- 07 15 00 81	G 1/8	8	bistabiilne	3*