

K-WV 5/2 MANU K DREHHEBEL

5/2-way pilot valves, manually operated, with short wing lever

HANSA FLEX

Omadused

| | |
|---------------------------------|---|
| Töörõhk | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Temperatuuri ulatus | -10 °C to +60 °C |
| Läbivool 6 bar ja 10 bar | 550 NI/min |
| Läbivool 6 bar ja 5 bar | 400 NI/min |
| Ventiilikorpus | Alumiinium |
| Vedru | Special steel |
| Kolb | Aluminium |
| Tihendusmaterjal | NBR |



Vihje

*3 valve positions only in conjunction with a second way valve.

Lisaandmed saate soovi korral.

Lisateave

Important: The scope of supply does not include a connector. Please order separately.

Artikkel

| Märgistus | Ühendus | Sümbol | Rakendus | Lülitusasendid |
|----------------|---------|--------|-------------|----------------|
| K- 07 15 02 37 | G 1/8 | 5 | monostable | 2 |
| K- 07 15 02 38 | G 1/8 | 6 | bistabiilne | 2 |
| K- 07 15 02 39 | G 1/8 | 7 | monostable | 3* |
| K- 07 15 02 40 | G 1/8 | 8 | bistabiilne | 3* |