


K-BKR KL SERIE 375

Ball valves, 375 series

HANSA FLEX

Omadused

| | |
|-----------------------------|---|
| Töörõhk | max. 70 bar (depending on temperature and nominal size) |
| Umbkaudsed väärtused | G 1/4 to G 1: 20 °C: 70 bar, 60 °C: 65 bar, 100 °C: 45 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar G 1 1/4 to G 1 1/2: 20 °C: 70 bar, 60 °C: 55 bar, 100 °C: 35 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar G 2: 20 °C: 60 bar, 60 °C: 40 bar, 10 |
| Töötemperatuur | 200 °C at 0 bar |
| Tihend | 15 % RPTFE (glass fibre reinforced PTFE) |
| Käsihoob | Stainless steel 1.4301 |



Vihje

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Lisaandmed saate soovi korral.

Tellimisinfo

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Lisateave

G thread acc. DIN EN ISO 228-1

Artikkel

| Märgistus | DN | Keere | A (mm) | B (mm) | L (mm) | Materjal |
|----------------|----|---------|-----------|-----------|-----------|-------------------------------|
| K- 07 30 15 36 | 5 | G 1/4 | 69,0 | 34,0 | 39,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 15 37 | 7 | G 3/8 | 83,0 | 38,0 | 44,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 15 38 | 10 | G 1/2 | 96,0 | 41,0 | 59,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 15 39 | 13 | G 3/4 | 96,0 | 45,0 | 60,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 29 80 | 16 | G 1 | 116,0 | 52,0 | 72,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 29 81 | 20 | G 1 1/4 | 116,0 | 57,0 | 77,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 29 82 | 25 | G 1 1/2 | 158,0 | 62,0 | 84,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 29 83 | 32 | G 2 | 158,0 | 68,0 | 100,0 | Stainless steel 1.4401/1.4408 |