

# K-MV O (NO) D 24 V DC STA

Normally open, (NO), directly operated, 24 V DC, standard type

**HANSA FLEX**

## Omadused

<b>Elektriühendus</b>	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
<b>Kaitse tüüp</b>	IP 65
<b>Aine temperatuur</b>	max. 80 °C when using water or oils; max. 90 °C when using with air
<b>Keerme kirjeldus</b>	G thread acc. DIN EN ISO 228-1
<b>Korpus, klapipesa</b>	Brass
<b>Sisedetail</b>	Stainless steel
<b>Tihend</b>	FPM



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Artikkel

Märgistus	Keere	maksimaalne töö rõhk (bar)	NW	A (mm)	B (mm)	C (mm)	Ehitustüüp
K- 07 30 01 86	G 1/8	7	3,0	70,0	40,0	76,0	2
K- 07 30 01 87	G 1/4	7	3,0	70,0	40,0	76,0	2
K- 07 30 01 88	G 3/8	7	5,0	85,0	52,0	92,0	2
K- 07 30 01 89	G 1/2	7	5,0	85,0	52,0	92,0	2