

# K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

**HANSA FLEX**

## Omadused

Töörõhk	0 - 35 bar
Aine temperatuur	-20 °C to +100 °C
Korpus	Brass
Kaitse ja tihend	Industrial glue, mid hardened



## Vihje

Couplings and distributors are also available separately  
Lisaandmed saate soovi korral.

## Kirjeldus

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

## Lisateave

Couplings and distributors are also available separately

## Artikkel

Märgistus	Ühendus	Ühendus	koosneb jaoturist
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

## on järgnevate toodete lisatarvikud

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«