


# K-S-BKR O ENTL ABSCHL

Safety ball valves, lockable, without relief port

**HANSA FLEX**

## Omadused

|                         |   |
|-------------------------|---|
| <b>Keerme kirjeldus</b> | Rp thread acc. to EN 10226  |
| <b>Temperatuur</b>      | -40 ° C up to max. +170 ° C; Warning: The freezing fluid in the system may damage the valve difficult |
| <b>Korpus</b>           | Nickel-plated brass   |
| <b>Käsihoob</b>         | Steel - PVC coated  |
| <b>Kuuli tihend</b>     | PTFE  |
| <b>Spindli tihend</b>   | PTFE  |



## Vihje

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Lisaandmed saate soovi korral.

## Kirjeldus

2/2-way safety ball valves made of nickel-plated brass. Specially designed for pneumatic applications. The ball valve can be locked manually. Full bore, heavy-duty type.

## Lisateave

The price does not include a padlock. Please order separately.

## Artikkel

| Märgistus      | DN | Keere    | PN (bar) | A (mm) | B (mm) | L (mm) |
|----------------|----|----------|----------|--------|--------|--------|
| K- 07 30 21 29 | 8  | Rp 1/4   | 65       | 82,0   | 39,5   | 51,0   |
| K- 07 30 21 30 | 10 | Rp 3/8   | 65       | 82,0   | 39,5   | 51,0   |
| K- 07 30 21 31 | 15 | Rp 1/2   | 65       | 100,0  | 43,0   | 61,0   |
| K- 07 30 21 32 | 20 | Rp 3/4   | 40       | 120,0  | 52,5   | 74,5   |
| K- 07 30 21 33 | 25 | Rp 1     | 40       | 120,0  | 57,0   | 90,5   |
| K- 07 30 21 34 | 32 | Rp 1 1/4 | 30       | 158,0  | 78,0   | 104,0  |
| K- 07 30 21 35 | 40 | Rp 1 1/2 | 30       | 158,0  | 85,0   | 117,0  |
| K- 07 30 21 36 | 50 | Rp 2     | 30       | 158,0  | 92,0   | 135,0  |

## Lisatarvikud

**K-VORHAENGESCHLOSS** Padlock