

# K-DRG DRV 200 STANDARD

DRV 200 pressure regulators, standard type

**HANSA FLEX**

## Omadused

|                             |   |
|-----------------------------|---|
| <b>Sisendrõhk</b>           | Max. 25 bar (Series 200 and 300 Series), Max. 40 bar (400 Series)     |
| <b>Temperatuuri ulatus</b>  | Max. 75 °C  |
| <b>Reduksiooni vahetork</b> | Max. 10:1 (200 Series), Max. 20:1 (300 Series), Max. 6:1 (400 Series) |
| <b>Tihendusmaterjal</b>     | NBR   |
| <b>Vedrukate</b>            | Pressed brass up to DN 25, Grey cast iron from DN 32                  |
| <b>Korpus</b>               | Red brass 2.1096.01   |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment. Good response characteristic because of only a few moving parts which hence minimal friction. Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

## Tellimisinfo

Tellida on võimalik ka muid mudelid.

## Lisateave

Tellida on võimalik ka muid mudelid.

## Artikkel

| Märgistus      | Keere   | Reguleerimisvahemik | Läbivoolu koefitsent (m <sup>3</sup> /h) | A (mm) | B        | C (mm) | D (mm) |
|----------------|---------|---------------------|--|--------|----------|--------|--------|
| K- 07 25 04 86 | G 1/4   | 1.5 - 8 bar         | 0,5                                      | 70,0   | 167,0 mm | 120,0  | 47,0   |
| K- 07 25 04 87 | G 3/8   | 1.5 - 8 bar         | 0,6                                      | 70,0   | 168,0 mm | 121,0  | 47,0   |
| K- 07 25 04 88 | G 1/2   | 1.5 - 8 bar         | 1,2                                      | 85,0   | 188,5 mm | 142,0  | 46,5   |
| K- 07 25 04 89 | G 3/4   | 1.5 - 8 bar         | 1,3                                      | 85,0   | 189,5 mm | 143,0  | 46,5   |
| K- 07 25 04 90 | G 1     | 1.5 - 8 bar         | 1,6                                      | 95,0   | 242,0 mm | 186,0  | 56,0   |
| K- 07 25 04 91 | G 1 1/4 | 1.5 - 8 bar         | 4,2                                      | 104,0  | 323,0 mm | 262,0  | 61,0   |
| K- 07 25 04 92 | G 1 1/2 | 1.5 - 8 bar         | 4,5                                      | 108,0  | 323,0 mm | 262,0  | 61,0   |
| K- 07 25 04 93 | G 2     | 1.5 - 8 bar         | 7,2                                      | 146,5  | 376,0 mm | 306,0  | 70,0   |

## Varuosad

K-VERSCHLEI-SATZ Set of wearing parts