K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

Omadused

Töövool	200 mA
Kaabli kruvikinnitus	M 20 x 1.5
Lülitusfunktsioon	Positive switching, PNP NO contact, damped or undamped in the end position
Kaitse tüüp	IP 67, acc. to DIN EN 60529
Temperatuuri ulatus	-20 °C to +70 °C
Korpus	Polyamide blue or black
Polt	Stainless steel 1.4301
Võll	Polyamide PA6, black
Kaas	Polycarbonate, transparent
Montaažisild	PA6 with 30 % glass fibre
Tihendid	EPDM and NBR
Tihendusmaterjal	NBR



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Artikkel

Märgistus	Pinge	Definitsioon
K- 07 30 29 06	9 V - 36 V DC	End position feedback, D 2 type with inductive 3-wire sensors

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.