K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

Omadused

Rakendamine	Calibration, testing and service unit
Täpsus	0,25% FS
Mõõteaine temperatuur	-20 °C to +80 °C
Keskkonnatemperatuur	-10 °C to +50 °C
Mõõteainega kokkupuutuvad osad	CrNi-steel with NBR seal
Korpus	Die-cast zinc



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

Lisateave

Further measuring ranges on request

Artikkel

Märgistus	Mõõteulatus	Ühendus
K- 07 20 12 70	-0.95 / +40 bar	G 1/4

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.