

# K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

**HANSA FLEX**

## Omadused

Töörõhk	Max. 6 bar (copper alloy), Max. 25 bar (stainless steel)
Tihendi Ø	26 mm
Kaitsetoru Ø	10 mm
Materjal	Copper alloy, CrNi-Steel 1.4571



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

For bimetallic thermometers in the »High quality« series.

## Artikkel

Märgistus	Ühendusniit	Paigalduspikkus	SW (mm)	Materjal
K- 07 20 11 35	G 1/2	L1 = 63 mm	27	Copper alloy
K- 07 20 11 36	G 1/2	L1 = 100 mm	27	Copper alloy
K- 07 20 11 37	G 1/2	L1 = 160 mm	27	Copper alloy
K- 07 20 11 38	G 1/2	L1 = 63 mm	27	CrNi steel 1.4571
K- 07 20 11 39	G 1/2	L1 = 100 mm	27	CrNi steel 1.4571
K- 07 20 11 40	G 1/2	L1 = 160 mm	27	CrNi steel 1.4571

## Lisatarvikud

K-BIMETALLTHERMOMETER 52-2 Bimetallic thermometers