

K-TR PVC SET

PVC air hose kits

HANSA FLEX

Omadused

Töötemperatuur -15 °C kuni +60 °C



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Flexible, pressure-resistant and non-abrasive standard hose, also resistant to ageing. Assembled with brass stem and brass quick disconnect coupling DN 7.2.

Artikkel

| Märgistus | Vooliku sise-Ø (mm) | Vooliku välis-Ø (mm) | Max. working pressure resistance at 23°C (bar) | Vooliku pikkus (m) |
|----------------|------------------------|-------------------------|---|-----------------------|
| K- 07 10 12 13 | 6,0 | 12,0 | 15 | 5 |
| K- 07 10 12 09 | 6,0 | 12,0 | 15 | 10 |
| K- 07 10 12 10 | 6,0 | 12,0 | 15 | 15 |
| K- 07 10 12 11 | 6,0 | 12,0 | 15 | 20 |
| K- 07 10 12 12 | 6,0 | 12,0 | 15 | 25 |
| K- 07 10 12 18 | 9,0 | 15,0 | 15 | 5 |
| K- 07 10 12 14 | 9,0 | 15,0 | 15 | 10 |
| K- 07 10 12 15 | 9,0 | 15,0 | 15 | 15 |
| K- 07 10 12 16 | 9,0 | 15,0 | 15 | 20 |
| K- 07 10 12 17 | 9,0 | 15,0 | 15 | 25 |
| K- 07 10 12 08 | 13,0 | 20,0 | 15 | 5 |
| K- 07 10 12 07 | 13,0 | 20,0 | 15 | 10 |