


# K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

**HANSA FLEX**

## Omadused

Töörõhk	Max. 12 bar, maximum static working pressure (non-pulsating)
Sisehülsside ja niplite töörõhk	0 to 35 bar
Õhu läbivool	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +60 °C
Korpus, ventiilikorpus	Nickel-plated brass
Ventiil	Brass
Vabastushülss	Plastic
Vedru, vedruseib, tihvtid, kuulid	Stainless steel
Tihendusmaterjal	NBR



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

## Artikkel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 03 04	Stem, I.D. 6	71,2	22
K- 07 35 03 05	Stem, I.D. 8	71,2	22
K- 07 35 03 06	Stem, I.D. 9	71,2	22
K- 07 35 03 07	Stem, I.D. 10	71,2	22
K- 07 35 03 08	Stem, I.D. 13	71,2	22

## Täiendavad elemendid

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,