

K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface

HANSA FLEX

Omadused

| | |
|------------------|-------------------------------|
| Vahendid | Air, neutral gases (filtered) |
| Töö rõhk | 1.5 - 8 bar |
| Töötemperatuur | +5 °C to +50 °C |
| Elektriühendus | Plug connector PG 9 |
| Korpus | Aluminium |
| Tihendusmaterjal | NBR |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Artikkel

| Märgistus | Pinge | Port 1 | Ühendus 3 + 5 | DN | Läbivool (L/min) |
|----------------|--------------|--------|---------------|----|------------------|
| K- 07 15 00 09 | 230 V, 50 Hz | G 1/4 | G 1/4 | 8 | 1370 |
| K- 07 15 00 10 | 24 V DC | G 1/4 | G 1/4 | 8 | 1370 |
| K- 07 15 00 11 | 230 V, 50 Hz | G 3/8 | G 1/4 | 10 | 1650 |
| K- 07 15 00 12 | 24 V DC | G 3/8 | G 1/4 | 10 | 1650 |