


# K-XVMK 5

Male connectors, conical male thread acc. to ISO 7-1, stainless steel

**HANSA FLEX**

## Omadused

Rõhuvahemik	Max. 25 bar
soovitatud voolikud	PTFE hose
Temperatuuri ulatus	-40 °C to +200 °C (depending on the hose quality and diameter)
Materjal	Roostevaba teras 1.4404
Tihend	Pure metal



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

## Artikkel

Märgistus	Keere	Vooliku jaoks	L1 (mm)	SW1 (mm)	SW2 (mm)
K- 07 40 30 19	R 1/8	6 mm / 4 mm	26,0	12	10
K- 07 40 30 20	R 1/8	8 mm / 6 mm	26,5	14	13
K- 07 40 30 17	R 1/4	6 mm / 4 mm	29,5	12	14
K- 07 40 30 18	R 1/4	8 mm / 6 mm	30,0	14	14
K- 07 40 30 16	R 1/4	10 mm / 8 mm	32,5	16	14
K- 07 40 30 21	R 3/8	10 mm / 8 mm	33,0	16	17