


# K-SVKM NW 7,6 STREAM LINE ST

Quick disconnect couplings DN 7.6, galvanised steel / brass, »stream line«

**HANSA FLEX**

## Omadused

Töörõhk	Max. 16 bar
Õhu läbivool	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Korpus	Steel
Vedru	Stainless-steel
Lükandhülss	Hardened and nickel-plated steel
Tihendusmaterjal	NBR



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

## Artikkel

Märgistus	Vooliku jaoks	Pikkus (mm)	SW1 (mm)	SW2 (mm)
K- 07 35 07 87	10 x 6,5	64,0	16	20
K- 07 35 07 88	12 x 8	68,0	19	20
K- 07 35 12 95	13,5 x 9,5	68,0	21	20
K- 07 35 07 89	16 x 11	68,0	24	24

## Täiendavad elemendid

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel