

K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

HANSA FLEX

Omadused

| | |
|----------------------------|---------------------------------------|
| Vahendid | Filtered, unlubricated compressed air |
| Töörõhk | 2.5 - 8 bar |
| Temperatuuri ulatus | -10 °C to +60 °C |
| Ühendus | Push-in fitting for pipe 4 mm |
| Rakendus | Pneumatic |
| Õhu läbivoolukogus 6 bar | 85 NI/min |
| max sisendsignaali ajanihe | 0,4 s |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Artikkel

| Märgistus | Definitsioon | Ühendus |
|----------------|---------------------------------------|-------------------------------|
| K- 07 15 26 09 | Two-hand safety valve without housing | Push-in fitting for 4 mm pipe |
| K- 07 15 26 10 | mounting element | - |