

K-MANO STAND U

Pressure gauges, CrNi steel, standard type, connection radial on bottom

HANSA FLEX

Omadused

Tüüp	131.11
Rakendamine	Bourdon-tube pressure gauge, CrNi steel type
Rakendus	For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction
Kvaliteediklass	2,5
Aine temperatuur	max. +100 °C
Keskkonnatemperatuur	-40 °C to +60 °C
Korpus	CrNi steel
Klaas	Polycarbonate



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Standard model manufactured entirely from CrNi steel, economical and reliable.

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 03 82	0 - 1.0 bar	40,0	G 1/4
K- 07 20 03 83	0 - 1.6 bar	40,0	G 1/4
K- 07 20 03 84	0 - 2.5 bar	40,0	G 1/4
K- 07 20 03 85	0 - 4.0 bar	40,0	G 1/4
K- 07 20 03 86	0 - 6.0 bar	40,0	G 1/4
K- 07 20 03 87	0 - 10.0 bar	40,0	G 1/4
K- 07 20 03 88	0 - 16.0 bar	40,0	G 1/4
K- 07 20 03 89	0 - 25.0 bar	40,0	G 1/4
K- 07 20 03 90	0 - 40.0 bar	40,0	G 1/4
K- 07 20 03 91	0 - 60.0 bar	40,0	G 1/4
K- 07 20 03 92	0 - 100.0 bar	40,0	G 1/4
K- 07 20 04 83	0 - 1.0 bar	50,0	G 1/4
K- 07 20 04 84	0 - 1.6 bar	50,0	G 1/4
K- 07 20 04 85	0 - 2.5 bar	50,0	G 1/4
K- 07 20 04 86	0 - 4.0 bar	50,0	G 1/4
K- 07 20 04 87	0 - 6.0 bar	50,0	G 1/4
K- 07 20 04 88	0 - 10.0 bar	50,0	G 1/4
K- 07 20 04 89	0 - 16.0 bar	50,0	G 1/4
K- 07 20 04 90	0 - 25.0 bar	50,0	G 1/4
K- 07 20 04 91	0 - 40.0 bar	50,0	G 1/4
K- 07 20 04 92	0 - 60.0 bar	50,0	G 1/4
K- 07 20 04 93	0 - 100.0 bar	50,0	G 1/4