


K-NIPPEL KUPPL NW7 IG VZ 1

Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female

HANSA FLEX

Omadused

Töörõhk	Max. 16 bar
Õhu läbivool	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Materjal	hardened zinc plated steel



Vihje

Lisaandmed saate soovi korral.

Artikkel

Märgistus	Definitsioon	SW (mm)
K- 07 35 12 89	Plug G 1/8 female	13
K- 07 35 02 52	Plug G 1/4 female	17
K- 07 35 02 53	Plug G 3/8 female	20
K- 07 35 02 54	Plug G 1/2 female	27

on järgnevate toodete täiendav element

K-SVKM NW 7,6 AG ST-MS VZ	Quick disconnect couplings DN 7.6, galvanised steel / brass, male
K-SVKM NW 7,6 IG ST	Quick disconnect couplings DN 7.6, galvanised steel / nickel-plated brass, female
K-SVKM NW 7,6 SCHL TUE ST VZ	Quick disconnect couplings DN 7.6, galvanised steel / brass, with hose connector
K-SVKM NW 7,6 STREAM LINE ST	Quick disconnect couplings DN 7.6, galvanised steel / brass, »stream line«