

K-SVKM NW 2,7 SCHL MS NI

Quick disconnect couplings DN 2.7, nickel-plated brass, with hose connector

HANSA FLEX

Omadused

| | |
|-------------------------------|--|
| Tööröhk | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Õhu läbivool | 165 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Aine temperatuur | -20 °C to +100 °C |
| Korpus, hülss, ventiliikorpus | Nickel-plated brass |
| Vedru, vedruseib, kuulid | stain less steel |
| Tihendusmaterjal | NBR |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

One-hand quick disconnect coupling, one side sealing, extremely compact, with a large bore and a small pressure drop. Ideal for: Medical & Dental equipment, instrumentation and control, laboratory equipment, chemical applications, small tools, analysis, miniature pneumatics, engineering.

Artikel

| Märgistus | Ühendus | Pikkus (mm) |
|----------------|-----------------------|----------------|
| K- 07 35 06 24 | Hose connection 4 x 3 | 34,0 |
| K- 07 35 06 25 | Hose connection 5 x 3 | 34,0 |
| K- 07 35 06 26 | Hose connection 6 x 4 | 34,0 |