

K-SVKM NW 7,2 AG VA

Quick disconnect couplings DN 7.2, stainless steel, male

HANSA FLEX

Omadused

Töörõhk	1 - 35 bar and rough vacuum
Õhu läbivool	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-25 °C to +200 °C
Korpus, hüls, ventiilikorpus	Stainless steel 1.4305
Vedru, vedruseib	Stainless steel 1.4310
Lukustustihvt	Stainless steel 1.4401
Tihendusmaterjal	FKM



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

Artikkel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 07 59	G 1/4 male	43,0	22
K- 07 35 07 60	G 3/8 male	43,0	22
K- 07 35 07 61	G 1/2 male	46,0	24

Täiendavad elemendid

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305