

K-SVKM NW 7,2 SCHL-TUE VA

Quick disconnect couplings DN 7.2, stainless steel, with hose stem

HANSA FLEX

Omadused

Töörõhk	1 - 35 bar and rough vacuum
Õhu läbivool	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-25 °C to +200 °C
Korpus, hüls, ventillikorpus	Stainless steel 1.4305
Vedru, vedruseib	Stainless steel 1.4310
Lukustustihvt	Stainless steel 1.4401
Tihendusmaterjal	FKM



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

Artikkel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 07 65	Stem, I.D. 6	59,0	22
K- 07 35 12 65	Stem, I.D. 8	59,0	22
K- 07 35 07 66	Stem, I.D. 9	59,0	22
K- 07 35 12 66	Stem, I.D. 10	59,0	22
K- 07 35 07 67	Stem, I.D. 13	59,0	22

Täiendavad elemendid

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305