

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Omadused

Töörõhk	0 - 35 bar
Õhu läbivool	2.100 l/min (at $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +40 °C
Keermega detail	Nickel-plated brass
Ventiilikorpus	Steel, QPQ treated
Vabastushülss	Extremely robust, ergonomic plastic
Ventiil, pesa	Brass
Vahendid	Only for clean compressed air
Tihendid	NBR
Vedru, vedruseib, kuulid	stain less steel



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Artikkel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 08 50	G 1/4 female	59,0	19
K- 07 35 08 51	G 3/8 female	59,0	19
K- 07 35 08 52	G 1/2 female	62,0	24

Täiendavad elemendid

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass