


K-SVKM NW 7,8 SCHL TUE VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, with hose stem

HANSA FLEX

Omadused

Tööröhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-15 °C to +200 °C
Korpus, hülss, ventiilikorpus	Stainless steel 1.4305
Vedru, vedruseib, kuulid	Stainless steel
Tihendusmaterjal	FKM



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

Artikel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 07 96	Stem, I.D. 6	73,5	19
K- 07 35 07 97	Stem, I.D. 8	73,5	19
K- 07 35 07 98	Stem, I.D. 9	73,5	19
K- 07 35 07 99	Stem, I.D. 10	73,5	19
K- 07 35 08 00	Stem, I.D. 13	73,5	19

Täiendavad elemendid

K-NIPPEL KUPPL NW7 AG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 1	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305