


# K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

**HANSA FLEX**

## Omadused

|                              |   |
|------------------------------|---|
| Töörõhk                      | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Õhu läbivool                 | 700 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Aine temperatuur             | -20 °C to +100 °C   |
| Korpus, hüls, ventiilikorpus | Brass   |
| Vedru, vedruseib, kuulid     | Stainless steel   |
| Tihendusmaterjal             | NBR   |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

## Artikkel

| Märgistus      | Ühendus       | Pikkus (mm) | SW (mm) |
|----------------|---------------|-------------|---------|
| K- 07 35 07 56 | Stem, I.D. 6  | 58,0        | 21      |
| K- 07 35 12 72 | Stem, I.D. 8  | 58,0        | 21      |
| K- 07 35 07 57 | Stem, I.D. 9  | 58,0        | 21      |
| K- 07 35 12 74 | Stem, I.D. 10 | 58,0        | 21      |
| K- 07 35 07 58 | Stem, I.D. 13 | 58,0        | 21      |