


# K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

**HANSA FLEX**

## Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	700 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Korpus, hüles, ventiilikorpus	Brass
Vedru, vedruseib, kuulid	Stainless steel
Tihendusmaterjal	NBR



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

## Artikkel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 07 56	Stem, I.D. 6	58,0	21
K- 07 35 12 72	Stem, I.D. 8	58,0	21
K- 07 35 07 57	Stem, I.D. 9	58,0	21
K- 07 35 12 74	Stem, I.D. 10	58,0	21
K- 07 35 07 58	Stem, I.D. 13	58,0	21