
K-DVST OHNE REGLER

Pressure booster without regulator



Omadused					
Sisendrõhk	2 - 10 bar				
Väljundrõhk	Max. 20 bar (regulated: max. 16 bar)				
Temperatuuri ulatus	-10 °C to +50 °C (40 mm bore), -10 °C to +60 °C (63 mm bore)				
Vahendid	Filtered, unlubricated or lubricated compressed air (if lubrication is used, it must be continuous)				
Tihendusmaterjal	NBR				
Rõhuregulaator	With plastic body				
Korpus	Aluminium, anodised				
Toru	Anodised aluminium jacket				
Montaaž	Any position, with 4 mounting holes				
P2:P1	2:1				





Vihje

For information about calculating the filling times for different tank sizes, refer to the above-mentioned data sheet available on our website Lisaandmed saate soovi korral.

Kirjeldus

Pressure multipliers (boosters) allow a separate compressed air store with up to double pressure to be installed for selected devices in a compressed air system without an external energy source, i.e. it is possible to work with a maximum pressure of 20 bar in a standard 10 bar system (maximum ratio 2:1). This is achieved using a double piston, which is operated by a combination of integrated check valves in such a way that the booster works automatically until the target pressure is reached in a compressed air tank and is then automatically switched off. A tank is always required to build up the pressure and store the compressed air!

Lisateave

Fixing bracket with nut

	-4:			
_	ıu	N	ke	

Märgistus	Ühendus	Kolbide Ø	Н	L	
		(mm)	(mm)	(mm)	
K- 07 25 08 64	G 1/8	40,0	64,0	194,0	
K- 07 25 08 66	G 3/8	63,0	98,0	290,0	

Lisatarvikud

K-ZUBEH ERSATZ LUFT BOOSTER Accessories / spare parts for Air-air-multiplicator (booster)