


# K-SVKM NW 7,2 SCHL-TUE MS BL CL

Quick disconnect couplings DN 7.2, brass with a bare metal surface, with hose stem

**HANSA FLEX**

## Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Aine temperatuur	-20 °C to +100 °C
Korpus, hülss, ventiilikorpus	Brass
Tihendusmaterjal	NBR
Vedru, vedruseib, tihvtid	Stainless steel



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Artikkel

Märgistus	Ühendus	Pikkus (mm)
K- 07 35 07 45	Stem, I.D. 6	54,0
K- 07 35 07 46	Stem, I.D. 9	54,0
K- 07 35 07 47	Stem, I.D. 13	53,5
K- 07 35 07 48	Stem, I.D. 8	54,0
K- 07 35 07 49	Stem, I.D. 10	54,0