


K-SVKM NW 7,2 SCHL-ANSCHL MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut

HANSA FLEX

Omadused

Töörõhk	0 - 35 bar, maximum static working pressure (non-pulsating)
Õhu läbivool	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Aine temperatuur	-20 °C to +100 °C
Korpus, hüls	Nickel-plated brass
Ventiil	Brass with a bare metal surface
Vedru, vedruseib	Stainless steel 1.4310
Lukustustihvt	Stainless steel 1.4034
Tihendusmaterjal	NBR



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Artikkel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 12 67	Hose connection 6 x 4	58,0	21
K- 07 35 07 24	Hose connection 8 x 6	45,0	21
K- 07 35 07 25	Hose connection 10 x 8	49,0	21
K- 07 35 07 26	Hose connection 12 x 9	49,0	21

Täiendavad elemendid

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass