

# K-ZFL VENTILINSEL HDM

## Intermediate plates for HDM valve terminal

**HANSA****FLEX**

### Omadused

Vahendid	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Tööröhk	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Juhtimisrõhk	3 - 7 bar
Temperatuuri ulatus	-10 °C to +60 °C
Läbivool	200 NL/min (Ø 4), 500 NL/min (Ø 6), 800 NL/min (Ø 8)
Kontrollide arv	Max. 16 (e.g. 16 spring return valves)
Käsitei juhitav	Latching (bistable), Monostable (non-latching) version also available on request
Võimsustarve	0.6 W per pilot
Kaitse tüüp	IP 65



### Vihje

Lisaandmed saate soovi korral.

### Kirjeldus

These compact valve terminals, with a maximum flow rate of 800 NL/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

### Lisateave

Important: The scope of supply does not include a connector. Please order separately.

### Artikel

Märgistus	Funktsioon
K- 07 15 22 51	With additional pilots and exhausts
K- 07 15 22 52	With separate pilots (for multi-pressure systems)
K- 07 15 22 44	With separate exhausts (for multi-pressure system)