

K-T-STECK VERS DRE MINI PAR

Male branch tees, swivel type, mini, parallel thread

HANSA FLEX

Omadused

Töö rõhk	Max. 10 bar, vacuum
Rakendusvaldkond	Air, vacuum
soovitatud voolikud	PU or PA (nylon)
Vahendid	Suruõhk
Tavaline	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
Temperatuuri ulatus	0 °C to +60 °C
Tihenduspid	O-ring (NBR)
Materjal	Plastic, Nickel plated brass
Surverõngas	Plastic



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

Artikkel

Märgistus	Keere	vooliku välimise-Ø jaoks (mm)	L1 (mm)	L2 (mm)	SW
K- 07 40 23 04	M 3	3 mm	24,0	16,0	8 mm
K- 07 40 23 05	M 3	4 mm	28,0	17,2	8 mm
K- 07 40 23 06	M 5	3 mm	24,0	16,0	8 mm
K- 07 40 23 07	M 5	4 mm	28,0	17,2	8 mm
K- 07 40 23 08	M 5	6 mm	32,0	18,2	8 mm
K- 07 40 23 09	M 6	3 mm	24,0	16,5	10 mm
K- 07 40 23 10	M 6	4 mm	28,0	17,6	10 mm
K- 07 40 23 11	M 6	6 mm	32,0	18,6	10 mm
K- 07 40 23 12	G 1/8	4 mm	28,0	16,5	14 mm
K- 07 40 23 13	G 1/8	6 mm	32,0	16,5	14 mm
K- 07 40 23 14	R 1/8	4 mm	28,0	18,0	10 mm
K- 07 40 23 15	R 1/8	6 mm	32,0	19,0	10 mm