
K-WTEH SERIE ONE O DRS

Service units, »ONE« Series, without pressure switch



Omadused			
Sisendrõhk	lax. 10 bar		
Temperatuuri ulatus	-10 °C to +50 °C		
Vahendid	Suruõhk		
Kaitse tüüp	IP 65		
Töörõhk	0.5 - 8 bar		
Rõhulüliti	Changeover contact		
Filterelemendi pooride suurus	20 μm		
Läbivoolu väärtuse mõõtmine	At 6,3 bar and Δp = 1 bar		





Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Tellimisinfo

K- 07 25 13 81

G 1/2"

4000

165,5

This unit can also be supplied with many other combinations of functions and port sizes. We will be pleased to make you an offer to match your individual specification on request!

Artikkel						
Märgistus	Ühendus	Läbivool (L/min)	A (mm)	В	C (mm)	Pinge
K- 07 25 13 79	G 1/4	2400	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 80	G 3/8	3300	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)

35,0

24 V DC (for valves and pressure switch)

144,0 mm