


# K-VSTO POM

## Plugs

### Omadused

|                         |   |
|-------------------------|---|
| <b>Töörõhk</b>          | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)    |
| <b>Töötemperatuur</b>   | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| <b>Materjal</b>         | Acetalpolymerisat (POM)                           |
| <b>Tihendusmaterjal</b> | NBR   |



### Vihje

Lisaandmed saate soovi korral.

### Kirjeldus

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### Artikkel

| Märgistus      | Värv   | L1<br>(mm) | Liitmik<br>(mm) |
|----------------|--------|------------|-----------------|
| K- 07 40 29 11 | punane | 28,0       | 4               |
| K- 07 40 29 12 | punane | 28,0       | 5               |
| K- 07 40 29 13 | punane | 30,0       | 6               |
| K- 07 40 29 14 | punane | 31,0       | 8               |
| K- 07 40 29 15 | punane | 36,5       | 10              |
| K- 07 40 29 16 | punane | 38,5       | 12              |
| K- 07 40 29 17 | must   | 45,0       | 15              |
| K- 07 40 29 18 | must   | 41,5       | 18              |
| K- 07 40 29 19 | must   | 45,0       | 22              |
| K- 07 40 29 20 | must   | 56,0       | 28              |