


# K-MV G (NC) D 24 V DC H 1

Normally closed, (NC), directly operated, 24 V DC, for high pressures

**HANSA FLEX**

## Omadused

|                          |   |
|--------------------------|---|
| <b>Elektriühendus</b>    | device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket |
| <b>Kaitse tüüp</b>       | IP 65   |
| <b>Aine temperatuur</b>  | max. 80 °C when using water or oils; max. 90 °C when using with air   |
| <b>Keerme kirjeldus</b>  | G thread acc. DIN EN ISO 228-1  |
| <b>Korpus, klapipesa</b> | Brass   |
| <b>Sisedetail</b>        | Stainless steel   |
| <b>Tihend</b>            | FPM   |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Artikkel

| Märgistus      | Keere | maksimaalne töö rõhk<br>(bar) | NW  | A<br>(mm) | B<br>(mm) | C<br>(mm) | Ehitustüüp |
|----------------|-------|-------------------------------|-----|-----------|-----------|-----------|------------|
| K- 07 30 01 68 | G 1/8 | 30                            | 1,5 | 70,0      | 40,0      | 70,7      | 1          |
| K- 07 30 01 69 | G 1/4 | 30                            | 1,5 | 70,0      | 40,0      | 70,7      | 1          |
| K- 07 30 01 70 | G 3/8 | 30                            | 3,0 | 85,0      | 52,0      | 87,0      | 1          |
| K- 07 30 01 71 | G 1/2 | 30                            | 3,0 | 85,0      | 52,0      | 87,0      | 1          |