

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Omadused

Töörõhk	Max. 50 bar
Pealispind	Hot dip galvanised
Ühenduskeere	acc. ISO 7-1
Materjal	Zinc plated steel ST 37-2



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Artikkel

Märgistus	Keere	Pikkus (mm)
K- 07 40 35 71	R 1/4	40,0
K- 07 40 35 72	R 1/4	60,0
K- 07 40 35 73	R 1/4	80,0
K- 07 40 35 66	R 1/4	100,0
K- 07 40 35 67	R 1/4	120,0
K- 07 40 35 68	R 1/4	150,0
K- 07 40 35 69	R 1/4	180,0
K- 07 40 35 70	R 1/4	200,0
K- 07 40 35 95	R 3/8	40,0
K- 07 40 35 96	R 3/8	60,0
K- 07 40 35 97	R 3/8	80,0
K- 07 40 35 90	R 3/8	100,0
K- 07 40 35 91	R 3/8	120,0
K- 07 40 35 92	R 3/8	150,0
K- 07 40 35 93	R 3/8	180,0
K- 07 40 35 94	R 3/8	200,0
K- 07 40 35 63	R 1/2	40,0
K- 07 40 35 64	R 1/2	60,0
K- 07 40 35 65	R 1/2	80,0
K- 07 40 35 58	R 1/2	100,0
K- 07 40 35 59	R 1/2	120,0
K- 07 40 35 60	R 1/2	150,0
K- 07 40 35 61	R 1/2	180,0
K- 07 40 35 62	R 1/2	200,0
K- 07 40 35 87	R 3/4	40,0
K- 07 40 35 88	R 3/4	60,0
K- 07 40 35 89	R 3/4	80,0
K- 07 40 35 82	R 3/4	100,0
K- 07 40 35 83	R 3/4	120,0
K- 07 40 35 84	R 3/4	150,0
K- 07 40 35 85	R 3/4	180,0
K- 07 40 35 86	R 3/4	200,0
K- 07 40 35 39	R 1	40,0
K- 07 40 35 40	R 1	60,0
K- 07 40 35 41	R 1	80,0
K- 07 40 35 34	R 1	100,0
K- 07 40 35 35	R 1	120,0
K- 07 40 35 36	R 1	150,0

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Artikkel		
Märgistus	Keere	Pikkus (mm)
K- 07 40 35 37	R 1	180,0
K- 07 40 35 38	R 1	200,0
K- 07 40 35 55	R 1 1/4	40,0
K- 07 40 35 56	R 1 1/4	60,0
K- 07 40 35 57	R 1 1/4	80,0
K- 07 40 35 50	R 1 1/4	100,0
K- 07 40 35 51	R 1 1/4	120,0
K- 07 40 35 52	R 1 1/4	150,0
K- 07 40 35 53	R 1 1/4	180,0
K- 07 40 35 54	R 1 1/4	200,0
K- 07 40 35 47	R 1 1/2	40,0
K- 07 40 35 48	R 1 1/2	60,0
K- 07 40 35 49	R 1 1/2	80,0
K- 07 40 35 42	R 1 1/2	100,0
K- 07 40 35 43	R 1 1/2	120,0
K- 07 40 35 44	R 1 1/2	150,0
K- 07 40 35 45	R 1 1/2	180,0
K- 07 40 35 46	R 1 1/2	200,0
K- 07 40 35 79	R 2	40,0
K- 07 40 35 80	R 2	60,0
K- 07 40 35 81	R 2	80,0
K- 07 40 35 74	R 2	100,0
K- 07 40 35 75	R 2	120,0
K- 07 40 35 76	R 2	150,0
K- 07 40 35 77	R 2	180,0
K- 07 40 35 78	R 2	200,0
K- 07 40 50 93	R 2 1/2	80,0
K- 07 40 50 88	R 2 1/2	100,0
K- 07 40 50 89	R 2 1/2	120,0
K- 07 40 50 90	R 2 1/2	150,0
K- 07 40 50 91	R 2 1/2	180,0
K- 07 40 50 92	R 2 1/2	200,0
K- 07 40 50 99	R 3	80,0
K- 07 40 50 94	R 3	100,0
K- 07 40 50 95	R 3	120,0
K- 07 40 50 96	R 3	150,0
K- 07 40 50 97	R 3	180,0
K- 07 40 50 98	R 3	200,0