

K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

HANSA FLEX

Omadused

Tüüp	233.30
Rakendamine	Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Rakendus	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
Kvaliteediklass	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Aine temperatuur	max. +100 °C
Keskonnatemperatuur	-20 °C kuni +60 °C
Korpus	CrNi steel
Klaas	Laminated safety glass Ø 63 = Polycarbonate



Vihje

Lisaandmed saate soovi korral.

Artikkel

Märgistus	Mõõteulatus	Ø (mm)	Ühendus
K- 07 20 07 03	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 04	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 05	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 06	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 07	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 08	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 09	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 10	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 11	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 07 12	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 07 13	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 07 14	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 01 79	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 80	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 81	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 82	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 83	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 84	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 85	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 86	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 87	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 88	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 89	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 90	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 91	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 92	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 93	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 94	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 95	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 96	0 - 600.0 bar	100,0	G 1/2"