

K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

HANSA FLEX

Omadused

Tööröhk	max 10 baari
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Aine temperatuur	-20 °C to +150 °C
Korpus	Stainless steel 1.4404
Keere	Stainless steel 1.4404
Sisedetail	Stainless steel 1.4404
Nupp, ventiil	Stainless steel 1.4404
Tihendusmaterjal	FKM



Vihje

Not suitable for hitting / pulsating tools.

Lisaandmed saate soovi korral.

Kirjeldus

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Lisateave

Not suitable for hitting / pulsating tools.

Artikel

Märgistus	Ühendus	Pikkus (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25