

# K-L-STECKVER IG DREH

Banjo elbows with parallel female thread, swivel type

**HANSA FLEX**

## Omadused

|                            |  |
|----------------------------|--|
| <b>Töörõhk</b>             | Max. 15 bar, coarse vacuum   |
| <b>Rakendusvaldkond</b>    | Air, vacuum  |
| <b>soovitatud voolikud</b> | PU or PA (nylon)   |
| <b>Vahendid</b>            | Compressed air and all gases or liquids that are compatible with the materials |
| <b>Temperatuuri ulatus</b> | -20 °C to +80 °C   |
| <b>Tihenduspid</b>         | Parallel version: O-ring in housing  |
| <b>Materjal</b>            | Plastic, Nickel plated brass   |
| <b>Surverõngas</b>         | Plastic  |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikkel

| Märgistus      | Keere | vooliku välimise-Ø jaoks (mm) | L1 (mm) | L2 (mm) | SW    |
|----------------|-------|-------------------------------|---------|---------|-------|
| K- 07 40 05 66 | M 5   | 4 mm                          | 17,5    | 18,5    | 10 mm |
| K- 07 40 05 67 | M 5   | 6 mm                          | 18,7    | 19,7    | 12 mm |
| K- 07 40 05 79 | G 1/8 | 4 mm                          | 17,7    | 23,0    | 14 mm |
| K- 07 40 05 80 | G 1/8 | 6 mm                          | 18,7    | 24,4    | 14 mm |
| K- 07 40 05 81 | G 1/8 | 8 mm                          | 22,5    | 27,3    | 14 mm |
| K- 07 40 05 78 | G 1/8 | 10 mm                         | 27,2    | 27,3    | 17 mm |
| K- 07 40 05 75 | G 1/4 | 4 mm                          | 17,5    | 26,0    | 17 mm |
| K- 07 40 05 76 | G 1/4 | 6 mm                          | 18,7    | 27,4    | 17 mm |
| K- 07 40 05 77 | G 1/4 | 8 mm                          | 22,5    | 30,3    | 17 mm |
| K- 07 40 05 73 | G 1/4 | 10 mm                         | 27,2    | 34,3    | 17 mm |
| K- 07 40 05 74 | G 1/4 | 12 mm                         | 29,3    | 37,0    | 21 mm |
| K- 07 40 05 85 | G 3/8 | 6 mm                          | 18,7    | 28,7    | 21 mm |
| K- 07 40 05 86 | G 3/8 | 8 mm                          | 22,5    | 32,0    | 21 mm |
| K- 07 40 05 82 | G 3/8 | 10 mm                         | 27,2    | 36,3    | 21 mm |
| K- 07 40 05 83 | G 3/8 | 12 mm                         | 29,3    | 38,0    | 21 mm |
| K- 07 40 05 84 | G 3/8 | 16 mm                         | 32,5    | 40,5    | 24 mm |
| K- 07 40 05 71 | G 1/2 | 6 mm                          | 18,7    | 34,2    | 24 mm |
| K- 07 40 05 72 | G 1/2 | 8 mm                          | 22,5    | 34,3    | 24 mm |
| K- 07 40 05 68 | G 1/2 | 10 mm                         | 27,2    | 38,8    | 24 mm |
| K- 07 40 05 69 | G 1/2 | 12 mm                         | 29,3    | 40,5    | 24 mm |
| K- 07 40 05 70 | G 1/2 | 16 mm                         | 32,5    | 43,0    | 24 mm |