

# K-STECKVERSCHR IG SK

Male connectors, parallel female thread with outer hex

**HANSA FLEX**

## Omadused

|                |                    |
|----------------|--------------------|
| Töörõhk        | Max. 16 bar        |
| Töötemperatuur | -20 °C to +80 °C   |
| Materjal       | Nikeldatud messing |
| Surverõngas    | Hostaform          |
| Pingutusrõngas | Stainless steel    |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artikkel

| Märgistus      | Keere | vooliku välimise-Ø jaoks (mm) | L1<br>(mm) | SW    |
|----------------|-------|-------------------------------|------------|-------|
| K- 07 40 25 06 | M 5   | 3 mm                          | 15,7       | 7 mm  |
| K- 07 40 25 12 | G 1/8 | 4 mm                          | 26,2       | 10 mm |
| K- 07 40 25 13 | G 1/8 | 5 mm                          | 27,5       | 12 mm |
| K- 07 40 25 14 | G 1/8 | 6 mm                          | 27,1       | 12 mm |
| K- 07 40 25 15 | G 1/8 | 8 mm                          | 28,1       | 13 mm |
| K- 07 40 25 09 | G 1/4 | 4 mm                          | 28,6       | 10 mm |
| K- 07 40 47 15 | G 1/4 | 5 mm                          | 29,5       | 12 mm |
| K- 07 40 25 10 | G 1/4 | 6 mm                          | 29,3       | 12 mm |
| K- 07 40 25 11 | G 1/4 | 8 mm                          | 30,0       | 14 mm |
| K- 07 40 25 08 | G 1/4 | 10 mm                         | 31,8       | 16 mm |
| K- 07 40 25 16 | G 3/8 | 10 mm                         | 36,8       | 16 mm |
| K- 07 40 25 17 | G 3/8 | 12 mm                         | 37,0       | 19 mm |
| K- 07 40 25 07 | G 1/2 | 12 mm                         | 40,5       | 19 mm |