


# K-SCHOTT-STECK MINI

Bulkhead connectors, mini

**HANSA FLEX**

## Omadused

<b>Töörõhk</b>	Max. 10 bar, vacuum
<b>Rakendusvaldkond</b>	Air, vacuum
<b>soovitatud voolikud</b>	PU or PA (nylon)
<b>Vahendid</b>	Suruõhk
<b>Tavaline</b>	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
<b>Temperatuuri ulatus</b>	0 °C to +60 °C
<b>Materjal</b>	Plastic, Nickel plated brass
<b>Surverõngas</b>	Plastic



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

## Artikkel

Märgistus	Keere	vooliku välimise-Ø jaoks (mm)	L1 (mm)	SW
K- 07 40 50 12	M 8 x 0.75	3 mm	20,3	10 mm
K- 07 40 50 10	M 10 x 1.0	4 mm	24,0	12 mm
K- 07 40 50 11	M 12 x 1.0	6 mm	23,8	14 mm