

K-STECKVERSCHR AGR-K SK VA

Male connectors, conical male thread with outer hex

HANSA FLEX

Omadused

| | |
|----------------------|---|
| Töörõhk, pulseeriv | Max. 10 bar |
| Surve | Max. 15 bar (depending on pipe quality) |
| sobiv materjal | PVDF, PTFE, stainless steel, PA, PU |
| Tavaline | R thread acc. to ISO 7-1 |
| Keskkonnatemperatuur | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Materjal | Roostevaba teras 1.4404 |
| Tihendusmaterjal | FKM |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Artikkel

| Märgistus | Keere | vooliku välimise-Ø jaoks (mm) | L1 (mm) | SW |
|----------------|-------|-------------------------------|---------|-------|
| K- 07 40 24 10 | R 1/8 | 4 mm | 16,6 | 10 mm |
| K- 07 40 24 11 | R 1/8 | 6 mm | 21,2 | 12 mm |
| K- 07 40 24 12 | R 1/8 | 8 mm | 25,2 | 14 mm |
| K- 07 40 24 07 | R 1/4 | 4 mm | 20,6 | 14 mm |
| K- 07 40 24 08 | R 1/4 | 6 mm | 20,7 | 14 mm |
| K- 07 40 24 09 | R 1/4 | 8 mm | 23,7 | 14 mm |
| K- 07 40 24 06 | R 1/4 | 10 mm | 30,3 | 16 mm |
| K- 07 40 24 13 | R 3/8 | 10 mm | 23,5 | 17 mm |
| K- 07 40 24 14 | R 3/8 | 12 mm | 27,4 | 19 mm |
| K- 07 40 24 05 | R 1/2 | 12 mm | 27,4 | 22 mm |