

# K-L-STECKVER DREH AG-K

Male elbows, swivel type, conical male thread

**HANSA FLEX**

## Omadused

|                |                    |
|----------------|--------------------|
| Töörõhk        | Max. 16 bar        |
| Töötemperatuur | -20 °C to +80 °C   |
| Materjal       | Nikeldatud messing |
| Surverõngas    | Hostaform          |
| Pingutusrõngas | Stainless steel    |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artikkel

| Märgistus      | Keere | vooliku välimise-Ø jaoks (mm) | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|-------------------------------|------------|------------|-------|
| K- 07 40 27 08 | R 1/8 | 4 mm                          | 18,6       | 19,8       | 12 mm |
| K- 07 40 27 09 | R 1/8 | 6 mm                          | 21,9       | 19,8       | 12 mm |
| K- 07 40 27 10 | R 1/8 | 8 mm                          | 25,4       | 19,8       | 12 mm |
| K- 07 40 27 05 | R 1/4 | 4 mm                          | 18,6       | 22,6       | 14 mm |
| K- 07 40 27 06 | R 1/4 | 6 mm                          | 21,9       | 22,6       | 14 mm |
| K- 07 40 27 07 | R 1/4 | 8 mm                          | 25,4       | 23,6       | 14 mm |
| K- 07 40 27 04 | R 1/4 | 10 mm                         | 27,2       | 26,3       | 14 mm |
| K- 07 40 27 13 | R 3/8 | 8 mm                          | 23,6       | 27,1       | 17 mm |
| K- 07 40 27 11 | R 3/8 | 10 mm                         | 27,2       | 27,1       | 17 mm |
| K- 07 40 27 12 | R 3/8 | 12 mm                         | 30,0       | 27,1       | 17 mm |
| K- 07 40 27 03 | R 1/2 | 12 mm                         | 30,0       | 31,9       | 22 mm |