

# K-L-MEHRFACHVERT 2 DR AGR OR CLICK

Multiple union elbows with inner hex, 2 outlets, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## Omadused

|                |                    |
|----------------|--------------------|
| Töörõhk        | Max. 16 bar        |
| Töötemperatuur | -20 °C to +80 °C   |
| Materjal       | Nikeldatud messing |
| Surverõngas    | Hostaform          |
| O-rõngas       | NBR                |
| Pingutusrõngas | Stainless steel    |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artikkel

| Märgistus      | Keere | vooliku välimise-Ø jaoks (mm) | L1<br>(mm) | L2<br>(mm) | SW   |
|----------------|-------|-------------------------------|------------|------------|------|
| K- 07 40 26 50 | M 5   | 4 mm                          | 30,3       | 20,2       | 2 mm |
| K- 07 40 26 51 | M 5   | 6 mm                          | 30,3       | 23,5       | 2 mm |
| K- 07 40 26 55 | G 1/8 | 4 mm                          | 40,9       | 20,2       | 3 mm |
| K- 07 40 47 28 | G 1/8 | 5 mm                          | 42,0       | 25,0       | 5 mm |
| K- 07 40 26 56 | G 1/8 | 6 mm                          | 40,9       | 23,5       | 3 mm |
| K- 07 40 26 57 | G 1/8 | 8 mm                          | 40,9       | 24,8       | 3 mm |
| K- 07 40 26 53 | G 1/4 | 6 mm                          | 47,0       | 23,0       | 4 mm |
| K- 07 40 26 54 | G 1/4 | 8 mm                          | 47,0       | 26,5       | 4 mm |
| K- 07 40 26 52 | G 1/4 | 10 mm                         | 47,0       | 31,4       | 4 mm |